

## MFD 16/03/021

### Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.





|                              |                         |
|------------------------------|-------------------------|
| <b>Material</b>              | Thermoplastic elastomer |
| <b>Temp. range min</b>       | -40 °C                  |
| <b>Temp. range max</b>       | 100 °C                  |
| <b>Protection class</b>      | IP66 / IP68             |
| <b>Ø cable diameter min</b>  | 1 mm                    |
| <b>Ø cable diameter max</b>  | 2,1 mm                  |
| <b>Quantity of cable</b>     | 3                       |
| <b>BxL</b>                   | 13 x 9,7 mm             |
| <b>Product Color</b>         | RAL 9005                |
| <b>Using for cable gland</b> | SPRINT 16               |
| <b>Order no. RAL 9005</b>    | 10101014                |
| <b>Type</b>                  | MFD 16/03/021           |
| <b>Packing unit</b>          | 25                      |
| <b>ETIM-Classification</b>   | EC000441                |

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 3 cables Ø 1 - 2,1 mm

27.11.2020

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk