# Product Data Sheet

## 1210/5/EC



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---|---|
| **Material** | Polypropylene |
| **Material sealing gasket** | TPE |
| **Temp. range min** | -30 °C |
| **Temp. range max** | 100 °C |
| **Temperatures during install.** | -5 °C - 60 °C |
| **Protection class** | IP66 / IP67 |
| **Glow wire test** | 750 °C |
| **Voltage** | 690 V |
| **Rated current / A (Terminal)** | 57 A |
| **Rated cross section** | 10 mm² |
| **Terminals/poles** | 5-pole, 10,0 mm² |
| **Fixing** | 4 internal openings |
| **Ø cable diameter min** | 3 mm |
| **Ø cable diameter max** | 12 mm |
| **External dimensions LxWxH** | 160 x 140 x 81mm |
| **Using for cable gland** | |
| **Product Color** | RAL 9001 |
| **Order no. RAL 9001** | 1210/5/EC/W |
| **Type** | 1210/5/EC |
| **Packing unit** | 1 |
| **ETIM-Classification** | EC002600 |

06.11.2026

Your Contact:
**WISKA UK Ltd.**
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk



Other technical data on request / subject to change without notice