MFD 40/02/060-01/130

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Thermoplastic elastomer
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	4 mm
Ø cable diameter max	13 mm
Quantity of cable	3
BxL	35,6 x 18,3 mm
Product Color	RAL 9005
Using for cable gland	SPRINT 40
Order no. RAL 9005	10105687
Type	MFD 40/02/060-01/130
Packing unit	25
EAN number	4007686011524
Tariff number	39269097
ETIM-Classification	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: for 2 cables 4-6 mm Ø
and 1 cable 11-13 mm Ø

07.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice