# MFD 12/02/020 RW

Railway multiple sealing insert, TPE, white, M12



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---|---|
| **Material** | Thermoplastic elastomer |
| **Hazard level EN acc. 45545** | R22=HL3 / R23=HL3 / R24=HL3 |
| **Temp. range min** | -40 °C |
| **Temp. range max** | 100 °C |
| **Protection class** | IP66 / IP68 |
| **Ø cable diameter min** | 1 mm |
| **Ø cable diameter max** | 2 mm |
| **Quantity of cable** | 2 |
| **BxL** | 9,6 x 6,7 mm |
| **Using for cable gland** | SPRINT 12 |
| **Product Color** | RAL 9010 |
| **WISKA-Order no.** | 10105927 |
| **Type** | MFD 12/02/020 RW |
| **Packing unit** | 25 |
| **EAN number** | 4007686013894 |
| **Tariff number** | 40161000 |
| **ETIM-Classification** | EC000441 |

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

07.11.2026

Your Contact:
**WISKA UK Ltd.**
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk



Other technical data on request / subject to change without notice