# TKE/P 25/FFD/02/2.5 LG

Tails Kit Plastic M25 for flat cable



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---|---|
| **Material cable gland** | Polyamide |
| **Material sealing gasket** | EPDM |
| **Temp. range min** | -40 °C |
| **Temp. range max** | 100 °C |
| **Protection class** | IP66 |
| **Product Color** | RAL 7035 |
| **Thread type** | M |
| **Ø Connection thread D** | 25 |
| **Lead** | 1,5 |
| **Length screw-in thread L** | 10 mm |
| **Key width SW** | 29 mm |
| **Total length TL** | 38 mm - 47 mm |
| **Glow wire test** | 750 °C |
| **Type of cable anchorage** | A |
| **Install. torques fitting** | 10 N/m |
| **Install. torques cap nut** | 4 N/m |
| **Impact category** | 4 |
| **Order no. RAL 7035** | 10106241 |
| **Type** | TKE/P 25/FFD/02/2.5 LG |
| **Packing unit** | 1 |

Description:

IP68 Plastic cable gland for flat cable insert. ESKV 25/ FFD for 2 x 2.5 mm twin and earth. Kit contains insert and locknut.

06.11.2026

Your Contact:
**WISKA UK Ltd.**
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk



Other technical data on request / subject to change without notice