
BMCG-PU-C-12-LG

Conduit, galvanized steel, PU coated, corrugated, RAL 7035, NW12





Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

EN 45545 BRACE RoHS

Material	galvanized steel
Sheathing material 1st coating	PU
Surface	corrugated
Product Color	RAL 7005
Protection class	IP67
Temp. range min	-55 °C
Temp. range max	120 °C
NW	12
External diameter ED	15,7 mm
Ø inside	12 mm
Bending radius R	50 mm
Type	BMCG-PU-C-12-LG
WISKA-Order no.	10109072
Packing unit	30 m
EAN number	4007686080339
Tariff number	83071000
ETIM-Classification	EC001179


Recommended accessories

EMBMFS-C-12-16	10109092
EMBMFS-C-12-20	10109094

07.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice



Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice