
BMCG-PVC-C-BG-40

Conduit, galvanized steel core PVC coated and steel wire over-braid, NW40







Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	galvanized steel
Sheathing material 1st coating	PVC
Surface	corrugated
Protection class	IP67
Temp. range min	-15 °C
Temp. range max	70 °C
NW	40
External diameter ED	47,5 mm
Ø inside	39,5 mm
Bending radius R	160 mm
Type	BMCG-PVC-C-BG-40
WISKA-Order no.	10109085
Packing unit	25 m
EAN number	4007686080599
Tariff number	83071000
ETIM-Classification	EC001179


Recommended accessories

EMBMFS-S-40-40	10109113
EMBMFS-S-40-50	10109115

06.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice



Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice