EMBMFS-S-16-20

Metal Conduit fitting brass nickel-plated, NW16/M20, smooth



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material Conduit fitting	Brass nickel-plated
Material sealing gasket	PA
Protection class	IP67
Temp. range min	-45 °C
Temp. range max	145 °C
NW	16
Thread type	M
Ø Connection thread D	20
Lead	1,5
Length screw-in thread L	9 mm
Ø closure VD	33 mm
Ø inside	15,5 mm
Key width SW1	27 mm
Key width SW2	29 mm
Total length TL	33,5 mm
Using for Conduit	smooth
Torque nozzle	5 N/m
Torque cap nut	5 N/m
Type	EMBMFS-S-16-20
WISKA-Order no.	10109097
Packing unit	5
EAN number	4007686080896
Tariff number	74122000
ETIM-Classification	EC001180

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice

Recommended accessories

BMCG-PVC-S-16-BK	10109025
BMCG-PVC-S-16-LG	10109033
BMCG-PVC-S-16-BK-GT	10109041
BMCG-PVC-S-16-LG-GT	10109049

06.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice