MFD 50/10/070 RW

Railway multiple sealing insert, TPE, white, M50



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

SPRINT HL3 EN 45545 RoHS

Material	Thermoplastic elastomer
Hazard level EN acc. 45545	R22=HL3 / R23=HL3 / R24=HL3
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	5 mm
Ø cable diameter max	7 mm
Quantity of cable	10
BxL	43,6 x 22,9 mm
Using for cable gland	SPRINT 50
Product Color	RAL 9010
WISKA-Order no.	10110539
Type	MFD 50/10/070 RW
Packing unit	25
EAN number	4007686212181
Tariff number	39269097
ETIM-Classification	EC000441

Remarks:

- IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

06.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice