MFD 75/02/280 RW

Railway multiple sealing insert, TPE, white, M75



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

SPRINT HL3 EN 45545 RoHS

Material	Thermoplastic elastomer
Hazard level EN acc. 45545	R22=HL3 / R23=HL3 / R24=HL3
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	26 mm
Ø cable diameter max	28 mm
Quantity of cable	2
BxL	70,6 x 29,3mm
Using for cable gland	SPRINT 75
Product Color	RAL 9010
WISKA-Order no.	10113360
Type	MFD 75/02/280 RW
Packing unit	5
EAN number	4007686314175
Tariff number	40161000
ETIM-Classification	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

07.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice