
OSRA 50 / M50(M)*M32(F)

Ex d reduction adaptor, brass nickel-plated, M50-M32





Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Brass nickel-plated
Temp. range min	-60 °C
Temp. range max	110 °C
Protection class	IP66 / IP67
Type of protection	Ex eb, Ex tb, Ex db
Ex-Certificate	IECEx, ATEX
Thread type outer	M
Ø outer thread	50
Lead outer	1,5
Thread type inner	M
Ø inner thread	32
Lead inner	1,5
Length screw-in thread L	15 mm
Key width SW	57 mm
Collar diameter (E)	61 mm
Total length TL	22 mm
Equipment	Incl. connection thread gasket, incl. locknut
Surface	Nickel-plated
Order no. nickel-plated	50065660
Type	OSRA 50 / M50(M)*M32(F)
Packing unit	1
EAN number	4007685656603
Tariff number	74198090
ETIM-Classification	EC000938


Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice

06.11.2026

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice



Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice