

CW 32L

CW Pack Economy, brass gland and locknut, shroud



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Brass
Material shrouds	PVC
Packing unit	2
Temp. range min	-20 °C
Temp. range max	80 °C
Protection class	IP66
Thread type	M
Ø Connection thread D	32
Lead	1,5
Length screw-in thread L	10 mm
Ø cable diameter min	26 mm
Ø cable diameter max	33,5 mm
Ø cable below cable shield max	-26,5 mm
Key width SW	43 mm
Collar diameter (E)	50 mm
Total length TL	58 mm
Type	CW 32L
WISKA-Order no.	50101676

Recommended accessories

ORD-N 32	50108503
-----------------	----------

19.04.2024

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk



Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk